Nilfisk-ALTO Pressure Washers for Domestic Use

- How to choose the pressure washer that best suits your needs





transportation.

our PRO range.





Nilfisk-ALTO PRO





The Nilfisk-ALTO PRO range of products offers outstanding performance and is suitable for larger cleaning tasks round the house and for semi-professional tasks.



P 160.1-15 X-TRA

- For tough and frequent use
- Integrated hose reelManometer
- Flow and pressure regulation
- Compact nozzles
- Ceramic pistons -
- brass cylinder head • Removable integrated
- detergent tank • Steel armed hose
- Spray gun with quick
- connection and swivel
- Automatic start/stop

P 150.1-10 B

- For tough and frequent use
- Compact nozzles
- Brass cylinder headPressure regulation
- Removable integrated
- detergent tank
- Steel armed hose
- Spray gun with quick
- connection and swivel
- Automatic start/stop

Technical Data:

lechnical Data:				
Pump pressure	max	bar/MPa	10-160 / 1-16	10-150 / 1-15
	IEC		10-150 / 1-15	10-140 / 1-14
Water flow, Min. – Max.		l/h	570-650	540-610
Max. inlet temp.		°C	60	60
Power consumption		А	14.5	12.6
Voltage		V	230	230
Electric motor rated input		kW	3.3	2.9
Weight		kg	24.5	23
Dimensions L x W x H		mm	394 x 391 x 955	394 x 391 x 955
Hose length		m	15	10
Cable length		m	5	5
Standard Equipment:				
TORNADO PR nozzle			● 6411187	● 6411187
Powerspeed nozzle			● 6411054	● 6411054
Trolley			•	•
Hose reel			•	

Nilfisk-ALTO EXCELLENT





Accessories on page 108 Detergents on page 113

E 15.1.15 S.X.TRA E 15.1.0 E 15.1.0 E 10.1.5 X.TRA E 13.1.2 E 13.1

The Nilfisk-ALTO EXCELLENT range of domestic pressure washers offers along with a good performance level, a high level of comfort, flexibility and user-friendliness. The obvious solution for all kinds of outdoor cleaning tasks.

EXCELLENT		E 145.1-15 S X-TRA • Stationary use • Integrated hose reel • Integrated storage for cable and standard equipment • Pressure regulation • Spray gun with quick connection and swivel • Garden Hose reel • CLICK&CLEAN nozzle concept • Automatic start/stop	E 135.1-10 Integrated reel for hose and electric cable Pressure regulation Spray gun with quick connection and swivel CLICK&CLEAN nozzle concept Automatic start/stop	E 140.1-9 S X-TRA • Stationary use • Integrated hose reel • Pressure regulation • CLICK&CLEAN nozzle concept • Automatic start/stop	 E 130.1-8 Integrated storage for hose, cable and standard equipment Pressure regulation CLICK&CLEAN nozzle concept Automatic start/stop
	/MPa	10-145 / 1-14.5	10-135 / 1-13.5	10-140 / 1-14	10-130 / 1-13
I unip pressure max ban	.mu	10-135 / 1-13.5	10-125 / 1-12.5	10-135 / 1-13.5	10-125 / 1-12.5
Water flow, Min. – Max.	L/h	420-500	450-500	420-500	450-500
Max. inlet temp.	,	60	60	60	60
Power consumption	A	9	9	9	9
Voltage		230	230	230	230
Electric motor rated input	kW	2.1	2.1	2.1	2.1
Weight	kg	24.5	21.5	17.0	17.0
Dimensions L x W x H	mm	440 x 420 x 990	440 x 500 x 990	325 x 360 x 920	325 x 400 x 920
Hose length	m	15	10	9	8
Cable length	m	15	10	5	5
Standard Equipment:					
CLICK&CLEAN TORNADO PR nozzle		● 6411762	● 6411761	● 6411762	● 6411761
CLICK&CLEAN Powerspeed nozzle		• 6411133	● 6411133	● 6411133	● 6411133
CLICK&CLEAN Auto brush		• 6411131			
CLICK&CLEAN Foam sprayer, with bott	le	● 6411132	● 6411132	● 6411132	• 6411132
Trolley		• 6526250	● 6526250	•	•
Wall bracket		106411342		106411386	
Hose reel		• 106411343			

Nilfisk-ALTO COMPACT



Detergents on page 113



The Nilfisk-ALTO COMPACT range for typical domestic cleaning tasks like cleaning of flagstones, stairways, vehicles with a moderate use.

OMPACT

- C 120.1-10 X-TRA Integrated storage
- for hose, cable and
- standard equipment
- Pressure regulation
- CLICK&CLEAN
- nozzle concept
- Automatic start/stop • Hose reel for storage of hose
- C 120.2-6
- Integrated features
- Metal pump
- Integrated trolley Pressure regulation
- CLICK&CLEAN
- nozzle concept
- Storage of gun, nozzles, foam sprayer, hose and cable

C 110.1-5 X-TRA

- Compact unit
- with trolley • Metal pump
- Storage of hose, gun and nozzles

Technical	Data:
-----------	-------

echnical Dala:					
Pump pressure	max bar/MI	Pa 10-120 / 1-12	10-120 / 1-12	10-110 / 1-11	
	IEC	10-110 / 1-11	10-100 / 1-10		
Vaterflow, Min-Max	I,	′h 380-440	350-520	310-440	
Max. Inlet temp.		°C 40	40	40	
Power consumption		A 7.4	7.5	6.1	
/oltage		V 230	230	230	
electric motor rated input	k	W 1.7	1.7	1.4	
Veight	I	kg 15.5	8.4	6.7	
Dimensions L x W x H	m	m 295 x 400 x 850	267 x 276 x 816	246 x 269 x 635	
lose length		m 10	6	5	
Cable length		m 5	5	5	
itandard Equipment:					
LICK&CLEAN TORNADO PR	R nozzle	● 6411764	● 6411764		
CLICK&CLEAN Powerspeed	nozzle	● 6411133	• 6411133		
CLICK&CLEAN Foam spraye	r, with bottle	● 6411132	• 6411132		
rolley		•	•	•	
Aultispeed nozzle				126486825	
Powerspeed nozzle				126486826	
oam sprayer and bottle				• 126486828	
lose reel		•			

Steamers



fisk



▲ STEAMTEC 5 IH

▲ STEAMTEC 520

▲ STEAMTEC 312

STEAMTEC 312

powerful heater

it very efficient

Stainless steel boiler

Steamers are the most efficient way to loosen and remove dirt, stains on car seats, carpets and furniture. And when it is time to clean the kitchen or bathroom the steamer is ideal for removing dirt and debris and disinfecting in one easy step.

- Refilling is possible while
- working with steam due to the
- extra pressure less water tank
- Ironing function
- Stainless steel boiler · Short heating time due to
- the powerful heater
- High steam pressure makes
- it very efficient
- · Big rear wheels and front
- caster makes operation easy
- Large accessory range as standard
- · Meets all standards and it is very
- safety to use
- Compact design, easy storage

STEAMTEC 520

- · Steam control on the handle
- Ironing function
- · Stainless steel boiler
- Short heating time due
- to the powerful heater
- High steam pressure makes it very efficient
- · Big rear wheels and front
- caster makes operation easy
- Large accessory range as standard · Meets all standards and it is very
- safety to use
- · Compact design, easy storage
- makes operation easy Large accessory range as standard

• Easy to carry do to the smart

· Short heating time due to the

• High steam pressure makes

trigger gun/machine construction

· Meets all standards and it is very safety to use

• Easy to use, one button control

• Big rear wheels and front caster

Compact design, easy storage

. . .

Technical Data:				
Heating capacity	W	1500	1500	1600
Voltage	V	230	230	230
Water tank capacity	1	0.7 + 1.5	2	1.2
Max. operating pressure	bar	3.5	4.2	3.8
Steam temperature (boiler)	°C	140	150	145
Heat up time approx	min/l	Continual flow	6.8	6
Dimensions L x W x H	mm	395 x 285 x 250	385 x 275 x 220	360 x 245 x 250
Weight	kg	4.6	3.4	3.2
Hose length	m	2	2	2
Standard Equipment: Steam gun with hose	303000437	•	•	•
Detail nozzle	303000429		•	•
Brush adaptor	303000424		•	•
Detail brush, nylon		•	•	•
2 x Extension tubes	303000422	•	•	•
Floor brush	303000419	•	•	•
Window nozzle	303000426	•	•	•
			-	
Funnel	303000428		•	

Wet & Dry Vacuum Cleaners





The new AERO is a light and easy to transport machine with a corrosion-proof container. The AERO is as close as you can get to industrial equipment at a consumer price. With the new AERO the consumer get high performance in a small package with a huge working capacity and low working sound level.

The new Nilfisk-ALTO BUDDY range is a small package for everyone who needs to pick up Wet & Dry debris. BUDDY, for home, car, workshop and hobby: The powerful helper against any dirt, whether it is wet or dry.

Technical Data:			AERO 25-21 Push&Clean filter cleaning Convenience socket AutoOnOff Accessory holder Accessory organiser Cable hook Filter cartridge Wet filter 25 ltr con- tainer Chassis with two castors and two wheels	 Convenience socket Accessory holder Accessory organiser Cable hook Filter cartridge 	 Convenience socket Accessory holder Cable hook Filter cartridge Wet filter 	AERO 20-01 INOX • Push& Clean filter cleaning • Four castors • Accessory holder • Cable hook • Filter cartridge • Wet filter • Wet filter container	Push&Clean filter cleaning	holder • Cable hook • Filter cartridge • Wet filter	 18 l container Castor wheel Two wheels for 	BUDDY 15 • Wet filter • Filter bag • 15 I container • Castor wheel • Two wheels for stability • Accessory holder
Air flow rate		l/min.	3600	3600	3600	3600	3600	3600	3600	3600
Vacuum		mbar/kPa	190/19	190/19	180/18	180/18	180/18	180/18	160/16	160/16
Power	Pmax	W	1400	1400	1300	1300	1300	1300	1300	1300
Mains connection		V/~/Hz	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50
Working sound level		dB(A)	67	67	67	67	67	67	69	69
Container volume		1	25	25	20	20	20	20	18	15
Dimensions L x W x H		mm	380 x 375 x 545	380 x 375 x 545	380 x 375 x 485	380 x 375 x 485	380 x 375 x 485	380 x 375 x 485	385 x 320 x 455	385 x 320 x 420
Weight w/o accessories		kg	5.9	5.9	5.7	6.7	5.7	5.7	4.2	3.9
Cable		m	5	5	5	5	5	5	5	5
Standard Accessories:										
Suction hose, Ø 32 mm			● 2.5 m	● 2.5 m	• 2.5 m	● 1.9 m	● 1.9 m	● 1.9 m	●1.9 m	● 1.9 m
Extension tube			● 2 x Alu Silber	● 2 x Alu Silber	• 2 x Alu Silber	• 2 x Plastic	• 2 x Plastic	• 2 x Plastic	• 2 x Plastic	• 2 x Plastic
Hand tube with suction	ontrol		•	•	•	•	•	•	•	•
Power tool adapter			•	•	•		•			
Floor nozzle						•	•	•	•	•
Turnable floor nozzle			•	•	•					
Crevice nozzle			•	•	•	•	•	•	•	
Universal nozzle			•	•	•	•	•	•		
Brush nozzle			•	•	•	•	•	•	•	•
Filter bag + Wet filter			• 302002404	• 302002404	• 302002404	• 302002404	• 302002404	• 302002404	• 302002403	• 302002403
Filter element			63990	• 63990	63990	• 63990	• 63990	63990		

Central Vacuum Systems





Nilfisk-ALTO CENTIX: Central vacuum system means that the unit is installed outside of the living area, vacuuming becomes much easier and more comfortable, the only thing you hear is a silent whispering. Since the dust is vented outside the house you also get a healthier home environment. The CENTIX 60 and 60 Premium can also be used as a mobile vacuum cleaner in the garage, for the car or for the terrace. Fitting is simple. Whether your home is brand new or centuries old, a central vacuum cleaner can be installed, without special knowledge or expertise.

		CENTIX 60 PREMIUM • For Central Vacuum System • High performance • Low noise • Large container volume	 CENTIX 60 For Central Vacuum System High performance Low noise Large container volume 	CENTIX 50 PREMIUM • For Central Vacuum System • High performance • Low noise • Large container volume • Display	 CENTIX 40 For Central Vacuum System High performance Low noise Large container volume 	 CENTIX 20 For Central Vacuum System High performance Low noise
Technical Data:						
Air flow rate	l/min.		3600	3300	3300	3120
Vacuum	mbar/KPa		230/23	240/24	240/24	220/22
Power Pmax	W	1500	1500	1700	1700	1500
Main connection	V/~/Hz	230/1~/50	230/1~/50	230/1~/50	230/1~/50	230/1~/50
Container volume	1	27	27	25	25	14
Dimensions L x W x H	mm	390 x 380 x 570	390 x 380 x 570	780 x 440 x 400	780 x 440 x 400	480 x 400 x 400
Weight w/c accessories	kg	10	10	6.7	6.5	5.5
Cable	m	5	5	3	3	3
Standard Equipment:						
Suction hose, 32 mm dia., 9 m v	vith Start/Stop	• 302001288		• 302001288		
Suction hose, 32 mm dia., 9	m		• 302001207		• 302001207	• 302001207
Curved hand tube		•	•	•	•	•
Telescopic tube, chrome		• 302001206	• 302001206	• 302001206	• 302001206	• 302001206
Combi floor nozzle		• 302000962	• 302000962	• 302000962	• 302000962	• 302000962
Crevice nozzle		● 6084	● 6084	● 6084	● 6084	● 6084
Universal nozzle		• 14295	• 14295	• 14295	• 14295	• 14295
Suction brush		● 5146	• 5146	• 5146	• 5146	• 5146
Hose holder		• 302001210	• 302001210	• 302001210	• 302001210	• 302001210
Filter bag		• 302000449	• 302000449	• 147 0771 010	• 147 0771 010	• 147 0770 010
Filter element		• 63990	• 63990	•	•	•